

USER GUIDE

LT-P2 LTP 2

Thank you for choosing Odyssey.



IMPORTANT!

Please read this User Guide before attempting to assemble and use stand.



Out of Box Inventory List

Qty	Item
1	12' TRIPOD STAND WITH SAFETY PIN
1	ADJUSTABLE INNER POLE FOR TRIPOD STAND
1	4' CROSSBAR with T-CONNECTOR and DUAL SUPPORT ARMS
1	HARDWARE BAG CONSISTS OF THE FOLLOWING:
1	HEXAGON ALLEN WRENCH
4	BOLTS
4	HEX NUTS
4	WING NUTS

Assembly Steps for the LTP2

1. Open tripod stand to the widest span possible. Next insert adjustable inner pole inside tripod through the top. After inner pole is installed, insert safety pin in hole.
2. Attach the 4' CROSSBAR with DUAL SUPPORT ARMS first and then tighten the T-CONNECTOR.
3. DO NOT attempt to mount or hang anything on your stand until your LTP2 is securely assembled with knobs tightened and safety pin installed.

Specifications

- Black high quality tripod stand
- Single T-bar with support bars & hanging bolts
- Tripod extends to 12 feet
- Folds up for easy transport
- Maximum load capacity 80lbs. evenly distributed
- Weight: 12 lbs.